

SAG™ 47 Silicone Antifoam Compound

Product Description

SAG 47 silicone antifoam compound may be an excellent candidate for boosting performance in non-aqueous systems, via reliable foam prevention. This moderately viscous compound may support an array of industrial applications at full as-supplied strength, in a solvent dispersion or in blends, depending on system needs. SAG 47 silicone antifoam compound helps prevent foam through addition to the system before foaming begins.

Key Features and Typical Benefits

- Material antifoam performance in non-aqueous systems
- Increased production throughput
- General-purpose reliability
- Meets EPA 40 CFR §180.910 requirements¹

Typical Physical Properties

Appearance	Translucent white
Active Ingredient Content	100% by weight
Viscosity at 25 °C (after stirring), cP	2,500
Specific gravity at 25 °C	0.988
Suitable Diluent	Process liquid, hydrocarbons
Shelf Life, months	12

Typical properties are average data and are not to be used as or to develop specifications.

Potential Applications

This antifoam's built-in versatility may allow its use in applications such as non-aqueous printing inks, agrochemicals, cleaners and detergents, lubricants, resin handling/manufacturing, sludge dewatering and chemical separations/distillations.

Potential Use in Agrochemical Products

Use SAG 47 silicone antifoam compound as received or dilute first with the process liquid (Table 1). Mix the antifoam when the package is opened to maximize results.

- Dilution: Mix 3 to 10 parts of the process liquid to 1 part antifoam; stir gently until a uniform mixture is reached. Ensure product uniformity over long storage periods by gentle periodic mixing
- For maximizing cost-effectiveness: Predilute SAG 47 silicone antifoam compound and add continuously at a process segment prior to foaming
- We suggest starting concentrations of 10 to 200 ppm

¹ The components meet the requirements of U.S. EPA regulation 40 CFR §180.920, and are therefore exempt from tolerances in food when used as an inert ingredient in agricultural applications in accordance with the other conditions of that regulation

Table 1: SAG 47 Silicone Antifoam Compound Concentrations and Parts per Million Equivalents

Concentration of SAG 47 Silicone Antifoam Compound (from container)	Parts per Million SAG 47 Silicone Antifoam Compound (as received)
1 liter in 1,000 liters	= 1000
1 liter in 2,000 liters	= 500
1 liter in 10,000 liters	= 100
1 liter in 20,000 liters	= 50

Conversion Factors: 1 liter = 0.264 gallons

Note: Test data. Actual results may vary.

Product Availability

Momentive Performance Materials, foam control agents are available in 5-gallon pails, 55-gallon drums and in bulk (upon request).

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Customer Service Centers

For additional information, please contact our Customer Service Team

AMERICAS	+1 800 295 2392 Toll Free* +704 805 6946 Direct Number
LATIN AMERICA	BRAZIL +55 11 4534 9650 Direct Number MEXICO +52 55 2169 7670 Direct Number *All American countries
EMEA – EUROPE, MIDDLE EAST, AFRICA & INDIA	EUROPE +390510924300 Direct Number INDIA, MIDDLE EAST & AFRICA +91 44 71212207 Direct Number* *All Middle Eastern countries, Africa, India, Pakistan, Bangladesh, Sri Lanka
ASIA PACIFIC	CHINA 800 820 0202 Toll Free +86 21 3860 4892 Direct Number JAPAN +81 3 5544 311 Direct Number KOREA +82 2 6201 4600 Direct Number SOUTH EAST ASIA, AUSTRALIA & NEW ZEALAND +60 3 9206 1543 Direct Number* *All East Asia countries (Malaysia, Singapore, Thailand, Indonesia, Vietnam, Philippines, Cambodia, Myanmar / other countries located in Pacific region)
Visit us at www.momentive.com	

DISCLAIMER - THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBE HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies.

Momentive and the Momentive logo are registered trademarks of Momentive Performance Materials Inc.

Copyright 2022 Momentive Performance Materials Inc. All rights reserved.



260 Hudson River Road
Waterford, NY 12188 USA
momentive.com

Current as of 2022-07-13 Printed in U.S.A